





FLAT SLAT AR405



SLAT PROFILES





FEATURES & BENEFITS

- Insulation
- Added security
- Wide range of colours
- Aesthetically pleasing
- Reduced greenhouse emissions
- Protection from the elements
- Light control
- Sound dampening

TECHNICAL SPECIFICATIONS

Weight (per m²)	4kg
Maximum Curtain Width	3.6m
Maximum Area (m²)	7.7
Gauge of Aluminium	0.32mm
Profile Slat Height	40mm
Profile Slat Thickness	9mm
Standard Guide Dimensions	53mm
Standard Bottom Bar Dimensions	40mm
Standard Axle	50mm circular

The Rollashield Residential Flat Slat has been designed specifically to suit the domestic roller shutter market in Australia but is also ideal with many commercial applications. The slat is roll formed in our Adelaide manufacturing facility to the highest of world standards using a German built roll forming machine which is the most advanced of its type in the world.

The Rollashield Residential Flat slat is a double walled cavity with PU foam injected during the roll forming process. This process provides economical strength and insulation qualities while maintaining exceptional working performance of the slat.

The flat profile is available in a wide range of colours, with profile lines on both sides offering an attractive finish from both the interior and exterior of the application.



BOX COLOUR OPTIONS















Ro ashield[®]

ROLLER SHUTTER COLOUR OPTIONS



White





Cream



Sand







Beige

Grey

Black







Brown

Green

Red





Woodland Grey

Deep Ocean Blue

Please note: Colours displayed are a guide only and have been matched as closely as possible. Due to the nature of the printing process, some degree of colour variation may occur. We recommend that you use production line prepared samples for final colour selection or approval.

BOXING OPTIONS

SQUARE BOXING (SQ45)

Sizes Available	Maximum Overall Height
150mm	900mm
165mm	1400mm
180mm	1700mm
205mm	2300mm
230mm	3000mm
250mm	3600mm

Please note: Only when using Ozroll's 50mm circular axle.

CONTROL OPTIONS

MANUAL







Strap

Winder

Spring Assist

MOTORISED







E-Trans



SOMFY 240V with Inis Uno



SOMFY 240V with Key Switch



SOMFY 240V RTS with Transmitter



SOMFY 240V with CSI override

ROUND BOXING (RD360)

Sizes Available	Maximum Overall Height
140mm	900mm
160mm	1300mm
180mm	1700mm
200mm	2200mm
Places note: Only when using Orrel	l's 50mm sircular avla

Please note: Only when using Ozroll's 50mm circular axle.